



Wood Primer- Product Data Sheet

Production Description:

Wood Primer is a high quality linseed oil based primer for timber which is to be top coated with finishes suitable for application over a linseed oil or alkyd based primer.

Application:

Wood Primer is formulated for use with commercial machine designed to coat fascia boards and other pre-primed timber for the building industry.

Technical Information:

Colour	:	White or Pink
Volume solids	:	41%
Gloss Level	:	Matt
Specific Gravity	:	1.15 kg per lit.
Thinner	:	Mineral turpentine.

Theoretical Coverage:

10 sq.m. / Liter at 35 microns. Practical coverage depends on surface profile, method of application and dry film thickness.

Drying Time:

Drying Time : Touch dry: 4 to 6 hours.

(At 25° C & RH 60%)

Cooler temperature, higher film thickness or higher humidity. Conditions will lead to longer drying times.

Application Condition:

Directions for use

Surface Preparation: All surfaces should be sanded if necessary and dusted down before painting.

Application Details: Can be brushed or rolled as is or with small levels of thinner addition. Machine coating- use as manufactures directions.

Flammability & Transport

Highly flammable, Dangerous Goods Class 3.2, Flash Point 300C, UN 1263, PG III

Safety & Precautions

- Do not apply at temperature below 100 C.
- Provide adequate ventilation during use.
- Please refer to the Material Safety Data Sheet before using this primer.

Issued: Jan 2008.